

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

**UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office**

June 08, 2004

**THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A
FILING DATE.**

APPLICATION NUMBER: 60/460,970

FILING DATE: April 07, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/10526

REC'D 11 JUN 2004

WIPO

PCT

**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**



M. Tarver

**M. TARVER
Certifying Officer**

**PRIORITY
DOCUMENT**

**SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)**

BEST AVAILABLE COPY

04/07/03

1-800 U.S. PTO

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 10/31/2002. OMB 0851-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).


Express Mail Label No. EU424772977US

1036 U.S. PTO
60/460970

INVENTOR(S)					
Given Name (first and middle (if any))		Family Name or Surname		Residence (City and either State or Foreign Country)	
Reddy		Vangala		Albuquerque, New Mexico	
<input type="checkbox"/> Additional inventors are being named on the <u>N/A</u> separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
Low Profile Ceramic RF Filter					
Direct all correspondence to:					
<input checked="" type="checkbox"/> Customer Number		CORRESPONDENCE ADDRESS			
28168		→			
OR		Type Customer Number here			
<input type="checkbox"/> Firm or Individual Name					
Address					
Address					
City		State		ZIP	
Country		Telephone		Fax	
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification		Number of Pages		15	
<input checked="" type="checkbox"/> Drawing(s)		Number of Sheets		5	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76		<input type="checkbox"/> CD(s), Number			
		<input type="checkbox"/> Other (specify)			
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:		031677		\$160.00	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are:					

Respectfully submitted,

SIGNATURE



Date



TYPED or PRINTED NAME

Steven Weseman

TELEPHONE

(630) 924-3790

REGISTRATION NO.

(if appropriate)

Docket Number:

41,372

WC0157

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Low Profile Ceramic RF Filter

Technical Field

This invention relates to dielectric block filters for radio-frequency signals, and in particular, to monoblock multi-passband filters.

5 Background

Ceramic block filters offer several advantages over lumped component filters. The blocks are relatively easy to manufacture, rugged, and relatively compact. In the basic ceramic block filter design, the resonators are formed by typically cylindrical passages, called through-holes, extending through the block from the long narrow side to the opposite long narrow side. The block is substantially plated with a conductive material (i.e. metallized) on all but one of its six (outer) sides and on the inside walls formed by the resonator holes.

One of the two opposing sides containing through-hole openings is not fully metallized, but instead bears a metallization pattern designed to couple input and output signals through the series of resonators. This patterned side is conventionally labeled the top of the block, though the "top" designation may also be applied to the side opposite the surface mount contacts when referring to a filter in the board-mounted orientation. In some designs, the pattern may extend to sides of the block, where input/output electrodes are formed.

20 The reactive coupling between adjacent resonators is affected, at least to some extent, by the physical dimensions of each resonator, by the orientation of each resonator with respect to the other resonators, and by aspects of the top surface metallization pattern. Interactions of the electromagnetic fields within and around the block are complex and difficult to predict.

25 These filters may also be equipped with an external metallic shield attached to and positioned across the open-circuited end of the block in order to cancel undesired coupling between non-adjacent resonators and other components of the RF application device.

30 Although such RF signal filters have received widespread commercial acceptance since the 1980s, efforts at improvement on this basic design continued.

In the interest of allowing wireless communication providers to provide additional service, governments worldwide have allocated new higher RF frequencies for commercial use. To better exploit these newly allocated frequencies, standard setting organizations have adopted bandwidth specifications with
5 compressed transmit and receive bands as well as individual channels.

Coupled with the higher frequencies and crowded channels are the consumer market trends towards ever smaller wireless communication devices (e.g. handsets) and longer battery life. In particular, wireless device designers are concerned with reducing the board height, i.e. required clearance, of wireless components such as
10 filters. Technologies now competing with monoblock ceramic filters such as film bulk acoustic resonators (FBAR) in some cases offer reduced board height requirements. These technologies are relatively more expensive, however.

Accordingly, this invention pertains to providing smaller monoblock ceramic filters without sacrificing filtering performance.

15 Summary

This invention overcomes problems of the prior art by providing a multi-passband ceramic block RF filter having a lower required board height but low passband insertion loss.

The present invention provides a communication signal filter adapted for
20 connection to an antenna, a transmitter and a receiver. The filters are suitable for filtering an incoming signal from the antenna to the receiver and an outgoing signal from the transmitter to the antenna. Accordingly, the filters are suitable for providing a receiver signal passband and a transmit signal passband.

A communication filter according to the present invention includes a dielectric
25 block having a first and a second end portion and a central portion therebetween. On the dielectric block are provided a first and a second antenna coupling pad, a transmitter coupling pad and a receiver coupling pad. A plurality of coupled resonators extend through the block. A trap resonator extends through the block and is located in the central portion between the first and the second antenna
30 coupling pads such that the trap resonator provides increased attenuation outside of the desired passbands.

Such filters preferably include one or more additional trap resonators extending through the block and located at an end portion.

The filter's core of dielectric material has a first end, a second end, a top surface, a bottom surface and defines a plurality of through-hole each extending
5 between an opening on the top surface and an opening on the bottom surface. The surfaces of the core have a plurality of metallized areas. The metallized areas include a first input-output coupling area, a second input-output coupling area spaced apart from the first input-output coupling area along a length of the core between the first and second ends, a third input-output coupling area positioned
10 between the first input-output coupling area and the first end, and a fourth input-output coupling area positioned between the second input-output coupling area and the second end.

The metallized areas also include a relatively expansive area. The relatively expansive area extends contiguously from the sidewall of the through-holes towards
15 both the top surface and bottom surface of the core. The expansive area continues from within the through-holes over the bottom surface and the side surfaces of the core.

The first and second input-output coupling areas are spaced apart from each other but positioned toward the central portion of the block. The third and fourth
20 input-output coupling areas are positioned towards the first and second ends of the block, respectively.

In a preferred embodiment, the first and second coupling areas are for connection to a communication device antenna, and the third and fourth coupling areas are for connection to a communication device transmitter and receiver,
25 respectively.

The core configuration and the plurality of metallized areas together define a series of resonators including at least one through-hole resonator positioned between the first input-output coupling area and the second input-output coupling area. This centrally located resonator increases attenuation outside of the desired
30 passbands.

The core and metallized areas together also define a decoupler between the

first and second input-output coupling areas. The decoupler is preferably one of the plurality of through-holes having a metallized sidewall that is conductively connected to the expansive area at both the top surface and the bottom surface.

In a preferred embodiment, the communication filter includes four trap resonators. First and second trap resonators are provided on opposite sides of the decoupler and between the first and second input-output coupling areas. A third trap resonator is provided adjacent the third input-output coupling area, between the third coupling area and the first end of the block. A fourth trap resonator is likewise provided adjacent the fourth input-output coupling area, between the fourth coupling area and the second end of the block.

Brief Description Of The Figures

In the Figures,

FIG. 1 is an enlarged perspective view of a duplexing filter according to the present invention;

FIG. 2 is an enlarged top view of the filter of FIG. 1.

FIG. 3 is an enlarged perspective view of another embodiment of a duplexing filter;

FIG. 4 is an enlarged top view of the filter of FIG. 3.

FIG. 5 is a graph of insertion loss versus frequency for a transmit passband of the duplexing filter of FIG. 1;

FIG. 6 is a graph of insertion loss versus frequency for a receive passband of the duplexing filter of FIG. 1.

Detailed Description Of Preferred Embodiments

While this invention is susceptible to embodiment in many different forms, this specification and the accompanying drawings disclose only preferred forms as examples of the invention. The invention is not intended to be limited to the embodiments so described, however. The scope of the invention is identified in the appended claims.

Referring to FIGS. 1 and 2, an antenna duplexer or RF filter 10 includes an elongate, parallelepiped (or "box-shaped") core of ceramic dielectric material 12. Core 12 has three sets of opposing side surfaces: a top 14 and a bottom 16,

opposing long sides 18 and 20, and opposing narrow ends or sides 22 and 24. Core 12 has a central portion 21. The interface between sides 18, 20, 22 and 24 define parallel edges 26. Core 12 has a length C, width B and height A, the designations of which appear in the figures.

5 Core 12 defines a series of through-hole passageways 30A, 30B, 30C, 30D, 30E, 30F, 30G, 30H, 30I and 33, which each extend between openings on top surface 14 and bottom surface bottom 16. Through-holes 30A and 30H are located at ends 22 and 24. Through-holes 30D, 30E and 33 are located in central portion 21.

10 Core 12 is rigid and is preferably made of a ceramic material selected for mechanical strength, dielectric properties, plating compatibility, and cost. The preparation of suitable dielectric ceramics is described in U.S. Patent No. 6,107,227 to Jacquín et al. and U.S. Patent No. 6,242,376, the disclosures of which are hereby incorporated by reference to the extent they are not inconsistent with the present teachings. Core 12 is preferably prepared by mixing separate constituents in
15 particulate form (e.g., Al_2O_3 , TiO_2 , Zr_2O_3) with heating steps followed by press molding and then a firing step to react and inter-bond the separate constituents.

Filter 10 includes a pattern of metallized and unmetallized areas (or regions) 40. Pattern 40 includes an expansive, relatively wide area of metallization 42 and an
20 unmetallized area 44. Pattern 40 also includes multiple input-output coupling metallized areas 34, 35, 36 and 37. Specifically, pattern 40 has a transmitter coupling area 34, a receiver metallized coupling area 37, a first antenna input-output coupling area 35, and a second antenna input-output coupling area 36. Coupling areas 34 and 37 have corresponding surface mounting pads 34A and 37A on side
25 surface 18 and corresponding, respective extensions 34B and 37B onto top surface 14.

First and second antenna coupling areas 35 and 36 are preferably conductively linked to each other and a surface mount pad 38 by an interconnection area 39 of metallization. Coupling areas 35 and 36 have corresponding extensions
30 35B and 36B.

Pads 34A, 37A and 38 are provided for connecting filter 10 to other circuit

elements of an electronic device in a surface-mount configuration. Accordingly, the dimension identified with the reference "A" in the figures is the surface-mount height, i.e. board profile, of the filter.

5 Expansive metallized area 42 covers portions of top surface 14 and side surface 18, and substantially all of bottom surface 16, side surfaces 20, 22, 24 and the sidewalls 32 of through-holes 30. Expansive metallized area 42 extends contiguously from within the resonator holes 30 towards both top surface 14 and bottom surface 16. Area 42 serves as a local ground.

10 Core 12 and pattern 40 together form the series of through-hole resonators 31A, 31B, 31C, 31D, 31E, 31F, 31G, 31H and 31I. Resonator pads 60A, 60B, 60C, 60D, 60F, 60G, 60H and 60I are located on top surface 14 and are a portion of metallized area 42 and connected to metallization on sidewalls 32.

15 A key feature of the present invention is the presence of at least one centrally located trap resonator. Filter 10 includes two centrally positioned trap resonators, 31D and 31E. Both resonators 31D and 31E are located between the first and second antenna coupling areas 35 and 36. As used herein to describe the relative position of through-holes, resonators and metallized areas, the term "between" is a reference to the substantial alignment of features of the filter over the length C of the block between end 22 and end 24. For example, the position of through-hole 30A is
20 between surface mount pad 34A and end 22 even though pad 34A is offset (on side 18) from the series of through-holes 30. Furthermore, the alignment of features described using the term "between" may include a reasonable amount of overlap.

25 A decoupler 47 is provided between through-holes 30D and 30E to reduce inductive and other electromagnetic coupling between resonators 31D and 31E. Decoupler 47 is provided in the form of a through-hole 33 having a metallized side wall connected to wide area 42 at bottom surface 16 and at top surface 14. Metallized through-hole 33 is connected to wide area 42 at top surface 14 by a metallization extension 62. Described in other words, doubly-connected metallized through-hole 33 creates a band of wide area 42 extending through the central
30 portion of core 12.

The trap resonators 31D and 31E are tuned to provide a resonate response at a frequency outside desired filter passbands. By placing the trap resonators outside the frequency passband of interest, additional "zeros" or poles of attenuation are created which offer greater design flexibility and latitude, and a desirable
 5 frequency response.

Filter 10 preferably also includes a trap resonator towards end surfaces 22 and 24. Through-holes 30A and 30I form trap zeros or trap resonators 31A and 31I. Trap resonator 31A is positioned between and adjacent to both transmitter coupling area 34 and core end surface 22. Trap resonator 31I is likewise positioned between
 10 but adjacent to both receiver coupling area 37 and core end surface 24.

Resonators 31B and 31C are electromagnetically coupled and positioned between transmitter coupling area 34 and first antenna coupling area 35. Resonators 31F, 31G and 31H are electromagnetically coupled and positioned between receiver coupling area 37 and second antenna coupling area 36.

15 Pattern 40 also includes an isolated metallized area 61 on top surface 14 in the shape of a bar or strip extending over the length of core 12 adjacent to resonator pads 60F, 60G and 60H.

The unmetallized area 44 is present on portions of top surface 14 and side surface 18. Unmetallized area 44 substantially surrounds (or circumscribes) the
 20 resonator pads 60A, 60B, 60C, 60D, 60E, 60F, 60G, 60H and 60I. Unmetallized area 44 also circumscribes transmitter coupling area 34, first and second antenna coupling areas 35 and 36, receiver coupling area 37, and strip-shaped area 61.

For ease of description, duplexer filter 10 can be divided at through-hole 33 into two sections of resonators 31, a transmitter section 72 and a receiver section
 25 74. Transmitter section 72 extends between first antenna coupling area 35 and end 22, while receiver section 74 extends in the opposite direction between second antenna coupling area 36 and end 24. Each section includes a plurality of resonators 31 and a respective input/output coupling area. More specifically, transmitter section 72 includes a transmitter coupling area 34, and receiver section
 30 74 includes a receiver coupling area 37.

The metallized areas of pattern 40 preferably comprise a coating of one or

more layers of a conductive metal. A silver-bearing conductive layer is presently preferred. Suitable thick film silver-bearing conductive pastes are commercially available from The Dupont Company's Microcircuit Materials Division.

5 The surface-layer pattern of metallized and unmetallized areas 40 on core 12 is preferably prepared by providing a rigid core of dielectric material, including through-holes, to predetermined dimensions. The outer surfaces and through-hole sidewalls are coated with one or more metallic film layers by dipping, spraying or plating.

10 The pattern of metallized and unmetallized areas is then preferably completed by computer-automated laser ablation of designated areas on core 12. This laser ablation approach results in unmetallized areas which are not only free of metallization but also recessed into the surfaces of core 12 because laser ablation removes both the metal layer and a slight portion of the dielectric material.

15 Alternatively, selected surfaces of the fully metallized core precursor are removed by abrasive forces such as particle blasting, resulting in one or more unmetallized surfaces. The pattern of metallized and unmetallized areas is then completed by pattern printing with thick film metallic paste.

20 Filters according to the present invention are optionally equipped with a metallic shield positioned across top surface 14. For a discussion of metal shield configurations, see U.S. Patent No. 5,745,018 to Vangala. The filters are typically later soldered to a printed circuit board that contains an RF transmitter, receiver and an antenna as in a cell phone, for example.

25 An alternative embodiment of an antenna duplexer or RF filter 200 is shown in FIGS. 3 and 4. RF filter 200 is similar to RF filter 10 except that first and second antenna coupling areas 235 and 236 are not conductively linked by metallization on the surface of core 212. First antenna coupling area 235 has a surface-mount pad 235A on side 218 and an extension 235B onto top surface 214. Second antenna coupling area 236 likewise has a surface mounting pad 236A and an extension 236B onto top surface 214. Surface mount pads 235A and 236A are preferably electrically
30 interconnected and linked to an antenna on the circuit board or other substrate of the host electronic device. Alternatively, pads 235A and 236A may be individually

connected to separate antennas. The other features of filter 200 are substantially the same as filter 10 as described herein above.

Example

A filter was simulated according to the embodiment shown in FIGS. 1 and 2 with the design parameters specified in Table I, below.

Table I

10	Filter length (side 24 to side 22)	13.50 mm
	Filter board height (side 18 to 20)	2.00 mm
	Filter width (side 14 to side 16)	6.50 mm
	Outgoing (transmit) signal passband	1850 to 1910 MHz
15	Incoming (receive) signal passband	1930 to 1990 MHz

The example filter was simulated using Microwave Office, Applied Wave Research, Inc. (El Segundo, CA). FIG. 5 is a type S₂₁ Scattering Parameter result from the simulation for the transmit section. The filter exhibited a maximum insertion loss for the desired transmit frequency band of about 3.3 dB. FIG. 6 is a type S₂₁ Scattering Parameter result from the simulation for the receive section. The filter exhibited a maximum insertion loss for the desired receive frequency band of about 4.6 dB.

S-parameters are ratios of reflected and transmitted traveling waves measured at specified component connection points. An S₂₁ data point or plot is a measure of insertion loss, a ratio of an output signal at an output connection to an input signal at an input connection, at one or a range of input signal frequencies. For a discussion of Scattering Parameters and associated test standards and equipment, please consult the following references: Anderson, Richard W. "S-Parameter Techniques for Faster, More Accurate Network Design," *Hewlett-Packard Journal*, vol. 18, no. 6, February 1967; Weinert, "Scattering Parameters Speed Design of High Frequency Transistor Circuits," *Electronics*, vol. 39, no. 18, Sept. 5, 1986; or Bodway, "Twoport Power Flow Analysis Using Generalized Scattering Parameters," *Microwave Journal*, vol. 10, no. 6, May 1967.

5 The simulated duplexer exhibited a significant improvement in attenuation at the target frequencies and only minor signal losses in the transmit and receive passbands. It provides a lower profile RF filter with low maximum insertion loss in the passband as well as a sharp transition to the stopbands.

10 Numerous variations and modifications of the embodiments described above may be effected without departing from the spirit and scope of the novel features of the invention. It is to be understood that no limitations with respect to the specific system illustrated herein are intended or should be inferred. It is, of course, intended to cover by the appended claims all such modifications as fall within the scope of the claims.

Claims:

I claim:

1. A communication filter comprising:
 - a dielectric block having a first and a second end portion and a central portion
 - 5 therebetween;
 - a first and a second antenna coupling pad on the block;
 - a transmitter coupling pad on the block;
 - a receiver coupling pad on the block;
 - a plurality of coupled resonators extending through the block;
 - 10 a trap resonator extending through the block and located in the central portion between the first and the second antenna coupling pads,
 - the trap resonator providing attenuation outside of a desired passband.
2. The communication filter according to claim 1 further comprising a second trap resonator extending through the block and located at an end portion.
- 15 3. An antenna duplexer comprising:
 - a dielectric block having three sets of paired opposed sides and a central portion;
 - a first and a second antenna coupling electrode on the elongate ceramic block in the central portion;
 - 20 a first section extending between the first antenna electrode and a first end of the block;
 - a second section extending between the second antenna electrode and a second end of the block, the second end opposing the first end,
 - each section having a plurality of coupled resonators extending between one
 - 25 set of the paired opposed sides;
 - a trap resonator in the central portion; and
 - a relatively expansive metallized area located on the block for providing a reference potential.
4. A communication signal filter comprising:
 - 30 a core of dielectric material having a first end, a second end, a top surface, a bottom surface and defining a plurality of through-holes each extending between an

opening on the top surface and an opening on the bottom surface;

a plurality of metallized areas on the core including,

a first input-output coupling area,

a second input-output coupling area spaced apart from the first input-output coupling area along a length of the core between the first and second ends,

a third input-output coupling area positioned between the first input-output coupling area and the first end,

a fourth input-output coupling area positioned between the second input-output coupling area and the second end,

wherein the core and the plurality of metallized areas together define at least one through-hole resonator positioned between the first input-output coupling area and the second input-output coupling area.

5. A communication signal filter comprising:

a core of dielectric material having a first end, a second end, a top surface, a bottom surface and defining a plurality of through-holes each extending between an opening on the top surface and an opening on the bottom surface;

a plurality of metallized areas on the core including,

a receiver coupling area,

a transmitter coupling area spaced apart from the receiver coupling area along a length of the core between the first and second ends,

a first antenna coupling area positioned between the receiver coupling area and the transmitter coupling area,

a second antenna coupling area positioned between the receiver coupling area and the transmitter coupling area,

a relatively expansive area,

wherein at least one of the plurality of through-holes is positioned between the first and second antenna coupling areas to define a trap resonator.

6. The filter of claim 5 further comprising a decoupler between the first and second antenna coupling areas.

7. The filter of claim 6 further wherein the decoupler is one of the plurality

of through-holes, said one having a metallized sidewall conductively connected to the expansive area at both the top surface and the bottom surface.

8. The filter of claim 5 wherein at least one of the plurality of through-holes is positioned between the first end of the block and the transmitter coupling area to define a trap resonator.

9. The filter of claim 5 wherein at least one of the plurality of through-holes is positioned between the second end of the block and the receiver coupling area to define a trap resonator.

10. The filter of claim 5 having four trap resonators.

11. A communication signal filter comprising:

a dielectric core having a series of through-holes and bearing a pattern of metallized and unmetallized areas, the dielectric core having first and second opposing outer portions and a central portion therebetween;

the dielectric core and the pattern together defining at least two signal paths each including an input coupling, an output coupling and a series of through-hole resonators therebetween,

the dielectric core and pattern together further defining a through-hole resonator in the central portion and outside the two signal paths.

12. In a communication filter including a plurality of coaxial resonators formed in a monoblock having through-holes and a metallization pattern, the monoblock having first and second ends and a central portion therebetween, the improvement which comprises:

a first and a second input-output coupling area in the central portion; and a trap resonator between the first and the second coupling areas.

13. In a communication filter including a plurality of coaxial resonators formed in a monoblock having through-holes and a metallization pattern, the monoblock having first and second ends and a central portion, the improvement which comprises:

a first and a second antenna coupling metallized area in the central portion; a decoupler between the first and the second antenna coupling areas; and a trap resonator between one of the first and the second antenna

coupling areas in the central portion and the decoupler.

Abstract

A low profile ceramic filter for connection to an antenna, a transmitter and a receiver. The filter filters an incoming signal from the antenna to the receiver and an outgoing signal from the transmitter to the antenna. The filter has a ceramic core with through-holes that extend between sides of the core. The through-holes form coupled resonators and trap resonators. Two trap resonators are located at ends of the block, and two of the trap resonators are located in a central portion of the block. The coupled resonators are located between the end trap resonators and the trap resonators in the central portion. The trap resonators have a resonant frequency that is outside of the desired passband such that trap zeros or poles are provided.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.